


MATERIAL SAFETY DATA SHEET

Share Corporation
P.O. Box 245013
Milwaukee, WI. 53224



GENERAL INFORMATION NUMBER: 414-355-4000
EMERGENCY TELEPHONE NUMBER: (800) 776-7192
CHEMTREC: (800) 424-9300

REVISION DATE: September 11, 2003
DATE OF ISSUE: December 3, 2003

I - Product Identification

Clean & Shine

PRODUCT CODE: 8230

CHEMICAL FORMULATION: Pressurized waterless wash & wax.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1

FLAMMABILITY: 2

REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

<u>SUBSTANCE</u>	<u>APPROX</u>	<u>OSHA</u>	<u>ACGIH</u>	<u>EPA 40 CFR:</u>			<u>CAS #</u>
	<u>%</u>	<u>PEL</u>	<u>TLV</u>	<u>302</u>	<u>355</u>	<u>372</u>	
Naptha	20.0-50.0	100 ppm	N/E	N	N	N	8030-30-6
Propane/Isobutane blend	10.0-20.0	N/E	800 ppm	N	N	N	68-476-86-8

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): 210*

SPECIFIC GRAVITY (WATER = 1): 0.75-0.80

VAPOR PRESSURE (mm Hg): N/D

VOC CONTENT (% by weight): N/D

VAPOR DENSITY (AIR = 1): > 1.0

EVAPORATION RATE (WATER = 1): N/D

SOLUBILITY IN WATER: Emulsion

pH: N/D

APPEARANCE AND ODOR: White, opaque semi-solid with faint petroleum smell.

* *Tested using the liquid component (excluding the propellant).

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 155*

(TEST METHOD): Closed cup

FLAME EXTENSION: N/D

FLAMMABLE LIMITS IN AIR (VOLUME %)

UPPER: N/D

LOWER: N/D

NFPA 30B Rating: N/D

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: Exposure to temperature above 120°F may cause bursting.

PRODUCT NAME: Clean & Shine

PRODUCT CODE: 8230

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers, acids and alkalis.

CONDITIONS TO AVOID: Excess heat and open flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY **INHALATION:** X **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X

INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None

EFFECTS OF OVEREXPOSURE

IF IN EYES: Redness, irritation, stinging, tearing.

IF ON SKIN: Irritation, redness, defatting of skin.

IF SWALLOWED: Gastrointestinal irritation, nausea, vomiting, diarrhea. Aspiration into lungs may cause chemical pneumonitis, which can be fatal.

IF INHALED: Symptoms are normally seen at air concentrations exceeding the recommended exposure levels. Irritation to the nose, lungs respiratory tract, dizziness, drowsiness, nausea, headache, unconsciousness. Intentional misuse of this product by concentrating and inhaling can be harmful or fatal.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Wash thoroughly with soap and water. Remove contaminated clothing and launder separately before reuse. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting. Do not leave victim unattended.

IF INHALED: Remove person to fresh air. Administer oxygen if breathing is difficult, administer artificial respiration if breathing has stopped. Obtain immediate medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.

WASTE DISPOSAL METHOD: Consult local environmental authorities. Dispose of cans in non-incinerated trash only.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION

LOCAL: Recommended

MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: Apron.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Do not expose to direct sunlight or store at temperatures above 120°F.

OTHER PRECAUTIONS: Keep out of reach of children. Do not puncture or incinerate container.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: Consumer Commodity

DOT CLASS: ORM-D

DOT ID NUMBER: None

DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: September 11, 2003

Prepared by: PMR

DATE OF ISSUE: December 3, 2003

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.